

Impeleri za pumpe unutrašnjih brodskih motora

DODACI:


G: brtva; GT: brtva + čep; GX: brtva + zrno;

X: zrno; CGT: ključ + brtva + čep;

N: uljeotporni nitrilni kaučuk; T: čep.




G - Brtva



O - O-ring



X - Zrno




C - Ključ



T - Čep






































































JABSCO unutarnje pumpe



| Kat.broj Impeler CEF | Impeler OSCULATI | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|----------------------------|----------------------|--|--|----------|------|--------|---------------------------------|-----------|-----------|---------|---------|------------|
| 16.194.00 | 16.185.00 New | - | 7273-0001; 6303-001 | 110 | | | 7,31/8 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.16 | 16.185.16 New | - | 21414-0001; 21411-0001; 1411-0001 1414-0001 | 113 | | | 8 | - | 31,3 | 11,9 | 6 | 1 |
| 16.194.22 | - | - | 14787-0001; 14609-0001; 1414-0001 | 130 | | | 8 | - | 31,75 | 12 | 6 | 3 |
| 16.194.29 | - | T: čepak | 17954-0001 | 109 | | | 16,85/19 | - | 66,5 | 50,6 | 8 | 20 |
| 16.194.32 | - | N: nitrilna guma otporna na ulje | 1414-0003 | 230 | | | 8 | - | 31,75 | 12 | 6 | 1 |
| 16.194.38 | 16.185.38 New | - | 6303-0001 | 138 | | | 7,31/8 | - | 51,3 | 22 | 6 | 8 |
| 16.193.73 | 16.186.73 New | N: nitrilna guma otporna na ulje | 6303-0003 | 238 | | | 7,31/8,07 | - | 51,3 | 22 | 6 | 8 |
| 16.193.98 | - | - | 9200-0001 | 106GT | | | 8 | - | 40 | 19 | 6 | 6 |
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | 4528-0001 | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.02 | 16.185.02 New | GX: Brtva + zrno | 22405-0001; 21951344 | 121 | | | 12 | 12 | 39,6 | 19,2 | 6 | 4 |
| 16.194.03 | 16.185.03 New | GX: Brtva + zrno | 653-0001 | 101 | | | 12,17 | 12,17 | 50,8 | 22,1 | 6 | 7 |
| 16.194.04 | 16.185.04 New | GX: Brtva + zrno | 673-0001 (6 blades); 21951344; 22222936 | 116 | | | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.31 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | 4528-0003 | 200 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |


Dodaci: G: brtva; GT: brtva + čep; GX: brtva + zrno; X: zrno; CGT: ključ + brtva + čep; N: uljeotporna nitrilna guma; T: čep; HD.K.

| Kat.broj Impeler CEF | Impeler OSCULATI | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|----------------------------|----------------------|---|---|----------|---|---|---------------------------------|--------------|-----------|-------|---------|------------|
| 16.194.33 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | 673-0003 | 216 |  |  | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.43 | 16.185.43 New | X: Zrno | 18653.0001 | 146 |  |  | 12,17 | - | 51,8 | 22 | 10 | 9 |
| 16.194.44 | - | GX: Brtva + zrno | 673.0001 | 156 |  |  | 12,7 | - | 51,8 | 22 | 10 | 9 |
| 16.194.73 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | 653-0003 | 201 |  |  | 12,17 | - | 50,8 | 22,1 | 6 | - |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 1210-0001; 3085-0001; 21951348; 21951346 | 107 |  |  | 14,29/16 | 14,29 /16 | 57 | 31,6 | 12 | 26 |
| 16.194.18 | - | HD.K | 17018-0001 | 187 |  |  | 14,29/16 | - | 65,2 | 76,65 | 8 | 11 |
| 16.194.23 | 16.185.23 New | - | 13554-0001 | 124 |  |  | 14,29/16 | - | 57 | 48,2 | 12 | 26 |
| 16.194.25 | - | GT: brtva + čepak | 22120-0001 | 104 |  |  | 14,29/16 | - | 57 | 50,2 | 12 | 26 |
| 16.194.34 | - | GT: brtva + čep; N: nitrilna guma otporna na ulje | 836-0003 | 205 |  |  | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.35 | - | GT: brtva + čep; N: nitrilna guma otporna na ulje | 1210-0003 | 207 |  |  | 14,29/16 | - | 57 | 31,6 | 12 | 26 |
| 16.194.36 | - | T: čepak; N: uljeotporna nitrilna guma | 17937-003 | 214 |  |  | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.40 | - | T: čepak | 6760-0001 | 115T |  |  | 22,5/25,4 | - | 95 | 88,5 | 9 | 13 |
| 16.194.45 | - | - | 31130-0061 | 161 |  |  | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.54 | - | - | 11979-0001 | 155 |  |  | 14,29/16 | - | 65 | 36,5 | 8 | 11 |
| 16.194.09 | 16.185.09 New | CGT: ključ + brtva + čep | 4568-0001 | 108 |  |  | 15,93/16 | - | 57 | 31,6 | 12 | 26 |
| 16.194.10 | - | T: čepak | 4598-0001 | 102 |  |  | 15,9/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.13 | 16.185.13 New | - | 22799-0001 | 129 |  |  | 12,75 | 12,75 | 50,8 | 22,1 | 6 | 7 |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | 18948-0001 | 120 |  |  | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |

| Kat.broj | Impeler | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|--|-------------------------------------|----------|---|---|------------------------------------|-----------|-----------|---------|---------|------------|
| Impeler CEF | OSCULATI | | | | | | | | | | | |
| 16.194.17 | - | GT: brtva + čepak | 18838-0001 | 103 |  |  | 15,9 | 15,9 | 62 | 31,7 | 12 | 22 |
| 16.194.39 | - | CGT: kluč + brtva + poklopac; N: uljerezistentna nitrilna guma | 4568-0003 | 208 |  |  | 15,9 | - | 57 | 31,6 | 12 | 26 |
| 16.194.42 | - | G: brtva | 18327-0001 | 167 |  |  | 16 | - | 65 | 51,2 | 12 | 20 |
| 16.194.67 | - | GT: brtva + čepak | 1877-0001; 22120-0001; 876120 | 133GT |  |  | 14,29 / 16 | - | 57,18 | 50,25 | 10 | 10 |
| 16.194.77 | - | - | 17240-0001; 18789-0001 | 144 |  |  | 22,5 / 25,4 | - | 117,6 | 88,5 | 9 | 28 |
| 16.194.78 | - | G: brtva | 18786-0001 | 153 |  | - | 20,2 | - | 117,6 | 88,5 | 9 | 28 |
| 16.194.80 | - | G: brtva | 17938-0001 | 163 |  |  | 22,5 / 25,4 | - | 95 | 95 | 12 | 15 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 920-0001 (8 blades); 21951356 | 106 |  |  | 14,29 / 16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.24 | 16.185.24 New | T: čepak | 17935-0001 | 135T |  |  | 22,5 / 25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.26 | 16.185.26 New | T: čepak | 17937-0001 | 114 |  |  | 14,29 / 16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.37 | 16.185.37 New | GT: brtva + čep; N: nitrilna guma otporna na ulje | 920-0003 | 206 |  |  | 14,29 / 16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.07 | - | GT: brtva + čepak | 836-0001 | 105 |  |  | 22,5 / 25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | 17936-0001; 21676-0001 | 145 |  |  | 22,5 / 25,4 | - | 95 | 88,5 | 12 | 15 |
| 16.194.52 | - | - | 17370-0001 | 152 |  |  | 20,2 | - | 95 | 88,5 | 12 | 15 |
| 16.194.57 | - | GT: brtva + čepak | 17018-0001 B | 177.GT |  |  | 14,29 / 16 | - | 65,2 | 75,65 | 8 | 11 |
| 16.194.15 | - | GT: brtva + čepak | 18958-0001 | 164 |  |  | 20,1 | - | 84 | 73,5 | 12 | 24 |





















Dodaci: G: brtva; GT: brtva + čep; GX: brtva + zmo; X: zmo; CGT: kluč + brtva + čep; N: uljeotporna nitrilna guma; T: čep; HD.K.

JOHNSON brodskih motora

















| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|--|--------------------|----------|------|--------|---------------------------------|--------------|--------|-------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | 09-0806B | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.02 | 16.185.02 New | GX: Brtva + zrno | 09-808B | 121 | | | 12 | 12 | 39,6 | 19,2 | 6 | 4 |
| 16.194.03 | 16.185.03 New | GX: Brtva + zrno | 09-0810B | 101 | | | 12,17 | 12,17 | 50,8 | 22,1 | 6 | 7 |
| 16.194.04 | 16.185.04 New | GX: Brtva + zrno | 09-1026B | 116 | | | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.38 | 16.185.38 New | - | 09-824P; 09-834 | 138 | | | 7,31/8 | - | 51,3 | 22 | 6 | 8 |
| 16.194.31 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | 09-0806B-9 | 200 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.33 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | 09-1026B-9 | 216 | | | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.73 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | 09-810B-9 | 201 | | | 12,17 | - | 50,8 | 22,1 | 6 | - |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 09-1027B | 107 | | | 14,29/16 | 14,29/ 16 | 57 | 31,6 | 12 | 26 |
| 16.194.23 | 16.185.23 New | - | 09-0812B | 124 | | | 14,29/16 | - | 57 | 48,2 | 12 | 26 |
| 16.194.34 | - | GT: brtva + čepak | 09-1029B-9 | 205 | | | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.35 | - | GT: brtva + čepak | 09-1027B-9 | 207 | | | 14,29/16 | - | 57 | 31,6 | 12 | 26 |
| 16.194.40 | - | T: čepak | 09-0802B | 115T | | | 22,5/25,4 | - | 95 | 88,5 | 9 | 13 |
| 16.194.60 | - | T: čepak | 09-820B | 186 | | | 22,5/25,4 | - | 96,5 | 130 | 12 | 15 |
| 16.194.62 | - | G: brtva | 09-821B | 162 | | | 22,5/25,4 | - | 65,8 | 80 | 12 | 21 |
| 16.194.84 | - | CG: klinčić + brtva | 09-801-B | 170 | | | 16 | - | 57 | 31,6 | 12 | 26 |
| 16.194.08 | - | GT: brtva + čepak | 09-814B | 145 | | | 22,5/25,4 | - | 95 | 88,5 | 12 | 15 |

Dodaci: G: brtva; GT: brtva + čep; GX: brtva + zrno; X: zrno; CGT: ključ + brtva + čep; CG: ključ + brtva; N: uljeotporna nitrilna guma; T: čep.

| Kat.broj | | Oprema | Ref.original | Ref.CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|----------------------|--------------|---------|---|---|---------------------------------|--------|--------|------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.41 | - | - | 09-1052S-9 | 232 |  |  | 8 | - | 44,6 | 13 | 6 | 5 |
| 16.193.73 | 16.186.73 New | - | 09-824P9 | 238 |  |  | 7,31 / 8,07 | - | 51,3 | 22 | 6 | 8 |
| 16.194.13 | 16.185.13 New | - | 09-827 | 129 |  |  | 12,75 | 12,75 | 50,8 | 22,1 | 6 | 7 |
| 16.194.51 | - | - | 09-1052B | 132 |  |  | 8 | - | 44,6 | 13 | 6 | 8 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 09-1028B | 106 |  |  | 14,29 / 16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.24 | 16.185.24 New | T: čepak | 09-0819B | 135T |  |  | 22,5 / 25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.26 | 16.185.26 New | T: čepak | 1028B | 114 |  |  | 14,29 / 16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.37 | 16.185.37 New | GT: brtva + čepak | 09-1028-B-9 | 206 |  |  | 14,29 / 16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.07 | - | GT: brtva + čepak | 09-1029B | 105 |  |  | 22,5 / 25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | 09-814B | 145 |  |  | 22,5 / 25,4 | - | 95 | 88,5 | 12 | 15 |


Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; T: čep.

AIFO brodskih motora

| Kat.broj | | Oprema | Ref. original | Ref.CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|--|------------------|---------|---|---|---------------------------------|--------------|--------|------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 4913429 | 107 |  |  | 14,29 / 16 | 14,29/ 16 | 57 | 31,6 | 12 | 26 |
| 16.194.36 | - | T: čepak; N: uljeotporna nitrilna guma | 8112772 | 214 |  |  | 14,29 / 16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.16 | 16.185.16 New | - | 828MTEA | 113 |  |  | 8 | - | 31,3 | 11,9 | 6 | 1 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 8108228 | 106 |  |  | 14,29 / 16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.26 | 16.185.26 New | T: čepak | 8112772 | 114 |  |  | 14,29 / 16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.37 | 16.185.37 New | GT: brtva + čep; N: nitrilna guma otporna na ulje | 8108228 | 206 |  |  | 14,29 / 16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.08 | - | GT: brtva + čepak | 8112451 | 145 |  |  | 22,5 / 25,4 | - | 95 | 88,5 | 12 | 15 |


Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.

SHERWOOD unutarnje pumpe



















| Kat.broj | | Oprema | Ref. original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|--|-----------------|----------|------|--------|-----------------------------|--------|--------|-------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.01 | 16.185.01 New | GX: Brtva + zрно | 9979 | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.10 | - | T: čepak | 10187; 12338 | 102 | | | 15,9/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | 10615K | 120 | | | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.17 | - | GT: brtva + čepak | 9959K | 103 | | | 15,9 | 15,9 | 62 | 31,7 | 12 | 22 |
| 16.194.31 | - | GX: brtva + zрно; N: Uljerezistentna nitrilna guma | 9979 | 200 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.36 | - | T: čepak | 18200 | 214 | | | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.42 | - | G: brtva | 15000K | 167 | | | 16 | - | 65 | 51,2 | 12 | 20 |
| 16.194.48 | 16.185.48 New | G: brtva | 9000K | 165 | | | 15,95 | - | 62,2 | 22,4 | 12 | 22 |
| 16.194.49 | - | G: brtva | 10077K | 166 | | | 12,8 | 12,8 | 56,6 | 19,8 | 12 | 26 |
| 16.194.63 | - | G: brtva | 27000K | 181 | | | 16,1 | - | 84 | 73 | 12 | 24 |
| 16.194.64 | - | GX: Brtva + zрно | 18000K | 182 | | | 20,7 | - | 94,5 | 101,5 | 12 | 15 |
| 16.194.55 | 16.185.55 New | G: brtva | 8000K | 190 | | | 12,2 | 12,2 | 19 | 40 | 6 | 4 |
| 16.194.75 | - | GX: Brtva + zрно | 29000K | 192 | | | 20 | - | 94,5 | 101,5 | 12 | 15 |
| 16.194.26 | 16.185.26 New | T: čepak | 18200 | 114 | | | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.15 | - | GT: brtva + čepak | 17000K | 164 | | | 20,1 | - | 84 | 73,5 | 12 | 24 |
| 16.194.61 | - | GX: Brtva + zрно | 22000K | 179 | | | 20,7 | - | 114,3 | 109,5 | 10 | 18 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; T: čep.




| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|---|--|----------|------|--------|-----------------------------|----------|--------|-------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | 803729; 875807-0; 3586494; 876554-7; 833550; 21972908; 3586494 | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.02 | 16.185.02 New | GX: Brtva + zrno | 875583; 833995; 21951342; 3586496 | 121 | | | 12 | 12 | 39,6 | 19,2 | 6 | 4 |
| 16.194.03 | 16.185.03 New | GX: Brtva + zrno | 876097 | 101 | | | 12,17 | 12,17 | 50,8 | 22,1 | 6 | 7 |
| 16.194.04 | 16.185.04 New | GX: Brtva + zrno | 8758C3; 3593659; 3596497; 21213660; 804696; 875808-8; 876690; 21951344; 897055; 3580066; 3586497; 22222936 | 116 | | | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.31 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | 803729; 875807-0; 876554-7 | 200 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 3862281; 875811-2; 877400; 21951346; 3858256; 3862567; 3855546; 3856039; 21951348 | 107 | | | 14,29/16 | 14,29/16 | 57 | 31,6 | 12 | 26 |
| 16.194.25 | - | T: čepak | 876120-7; 834794 | 104 | | | 14,29/16 | - | 57 | 50,2 | 12 | 26 |
| 16.194.27 | - | G: brtva | 3842786; 21213664; 21951352; 3593660; 21212794; 3584350; 3588914 | 178 | | | 14,29/16 | - | 57 | 48,2 | 12 | 26 |
| 16.194.34 | - | GT: brtva + čep; N: nitrilna guma otporna na ulje | 875660; 2430184; 875736; 807904 | 205 | | | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.62 | - | G: brtva | 876771; 3887761; 21951358; 22994993 | 162 | | | 22,5/25,4 | - | 65,8 | 80 | 12 | 21 |
| 16.194.56 | 16.185.56 New | GT: brtva + čepak | 21213660; 3862567; 21951348 | 189 | | | 16 | - | 57 | 32,05 | 12 | - |
| 16.194.09 | 16.185.09 New | CGT: klijuč + brtva + čep | 875575-3; 831182 | 108 | | | 15,93/16 | - | 57 | 31,6 | 12 | 26 |
| 16.194.10 | - | T: čepak | 818680 | 102 | | | 15,9/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | 835874 | 120 | | | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.17 | - | GT: brtva + čepak | 835512-5; 3854286 | 103 | | | 15,9 | 15,9 | 62 | 31,7 | 12 | 22 |
| 16.194.19 | - | - | 3555413-8 | 380 | | | 10 | - | 39,6 | 14,3 | 12 | 14 |
| 16.194.67 | - | G: brtva | 834794; 876120 | 133GT | | | 14,29/16 | - | 57,18 | 50,25 | 10 | 10 |
| 16.194.80 | - | G: brtva | 3830459 | 163 | | | 22,5/25,4 | - | 95 | 95 | 12 | 15 |

















Dodaci: G: brtva; GT: brtva + čep; GX: brtva + zrno; X: zrno; CGT: klijuč + brtva + čep; CG: klijuč + brtva; N: uljeotporna nitrilna guma; T: čep.

| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|---|---|----------|---|---|-----------------------------|--------|--------|-------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.84 | - | CG: klinčić + brtva | 875575-3; 831182; 21951350 | 170 |  |  | 16 | - | 57 | 31.6 | 12 | 26 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 877061; 875593-6; 3841697; 21951356; 801277; 825941 | 106 |  |  | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.24 | 16.185.24 New | T: čepak | 877066; 21951362 | 135T |  |  | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.26 | 16.185.26 New | T: čepak | 3588475 | 114 |  |  | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.37 | 16.185.37 New | GT: brtva + čep; N: nitrilna guma otporna na ulje | 877061-2; 875593-2; 3841697-2 | 206 |  |  | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.07 | - | GT: brtva + čepak | 875736-1; 2430184; 875660-3; 807904; 21730344; 21951360 | 105 |  |  | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | 875814; 875697; 21951364 | 145 |  |  | 22,5/25,4 | - | 95 | 88,5 | 12 | 15 |
| 16.194.57 | - | GT: brtva + čepak | 3583602; 3593573; 3588476; 3819486; 21730348; 3588474 | 177.GT |  |  | 14,29/16 | - | 65,2 | 75,65 | 8 | 11 |

Dodaci: G: brtva; GT: brtva + čep; GX: brtva + zrno; X: zrno; CGT: ključ + brtva + čep; CG: ključ + brtva; N: uljeotporna nitrilna guma; T: čep.








































MERCUISER brodskih motora




| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/vanjski) mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|--|-----------------------------------|----------|---|---|-----------------------------|--------|-------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | |
| 16.194.18 | - | HD.K | D183/254 | 187 |  |  | 14,29/16 | 65,2 | 76,65 | 8 | 11 |
| 16.194.20 | 16.185.20 New | X: Zrno | 312-11-008 | 123 |  |  | 12 | 52 | 25 | 6 | 7 |
| 16.194.21 | - | X: Zrno | 321-11-008 | 131 |  |  | 10 | 39,6 | 19,2 | 6 | 4 |
| 16.194.29 | - | T: čepak | 47-59362 Bravo I/11 47-59362-TQ01 | 109 |  |  | 16,85/19 | 66,5 | 50,6 | 8 | 20 |
| 16.194.36 | - | T: čepak; N: uljeotporna nitrilna guma | MB616; SF15/18; 6035413 | 214 |  |  | 14,29/16 | 65 | 50,1 | 10 | 20 |
| 16.194.45 | - | - | 47-831311350 | 161 |  |  | 22,5/25,4 | 95 | 63,1 | 12 | 15 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 47-801332602 | 106 |  |  | 14,29/16 | 65 | 50,2 | 8 | 11 |
| 16.194.26 | 16.185.26 New | T: čepak | MB616; SF15/18; 6035413 | 114 |  |  | 14,29/16 | 65 | 50,1 | 10 | 20 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.

YANMAR brodskih motora

| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|------------------|---|--|----------|---|---|---------------------------------|--------------|-----------|---------|---------|---------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.01 | 16.185.01 | New GX: Brtva + zrno | 104211-42070 104211-42071 | 100 |  |  | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.31 | - | GT: brtva + čep; N: nitrilna guma otporna na ulje | 104211-42070 | 200 |  |  | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.05 | 16.185.05 | New GT: brtva + čepak | 129470-42530 129470-42532 129670-42531 127610-42270 | 107 |  |  | 14,29/16 | 14,29 /16 | 57 | 31,6 | 12 | 26 |
| 16.194.23 | 16.185.23 | New - | 119773-42600- 1 | 124 |  |  | 14,29/16 | - | 57 | 48,2 | 12 | 26 |
| 16.194.45 | - | - | 119593-42200 119593-42202 | 161 |  |  | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.09 | 16.185.09 | New CGT: ključ + brtva + čep | 145410-46090 124310-46090 | 108 |  |  | 15,93/16 | - | 57 | 31,6 | 12 | 26 |
| 16.194.13 | 16.185.13 | New - | 124223-42091 124223-42092 128296-42070 128620-42200 | 129 |  |  | 12,75 | 12,75 | 50,8 | 22,1 | 6 | 7 |
| 16.194.14 | 16.185.14 | New GT: brtva + čepak | 128170-02070 | 120 |  |  | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.39 | - | GT: brtva + čep; N: nitrilna guma otporna na ulje | 124310-46090 | 208 |  |  | 15,9 | - | 57 | 31,6 | 12 | 26 |
| 16.194.16 | 16.185.16 | New - | 128176-42071 | 113 |  |  | 8 | - | 31,3 | 11,9 | 6 | 1 |
| 16.194.22 | - | - | 128170-42070 | 130 |  |  | 8 | - | 31,75 | 12 | 6 | 3 |
| 16.194.62 | - | G: brtva | 119574- 42550/52 | 162 |  |  | 22,5/25,4 | - | 65,8 | 80 | 12 | 21 |
| 16.193.73 | 16.186.73 | New GX: brtva + zrno; N: uljeotporna nitrilna guma | (pour Water Puppy) | 238 |  |  | 7,31/8,07 | - | 51,3 | 22 | 6 | 8 |
| 16.194.75 | - | GX: Brtva + zrno | 128620-42201 | 192 |  |  | 20 | - | 94,5 | 101,5 | 12 | 15 |
| 16.194.03 | 16.185.03 | New GX: Brtva + zrno | 128990-42200 | 101 |  |  | 12,17 | 12,17 | 50,8 | 22,1 | 6 | 7 |
| 16.194.48 | 16.185.48 | New G: brtva | 128620-42200 | 165 |  |  | 15,95 | - | 62,2 | 22,4 | 12 | 22 |
| 16.194.80 | - | G: brtva | 14867-42830 | 163 |  |  | 22,5/25,4 | - | 95 | 95 | 12 | 15 |
| 16.194.32 | - | N: nitrilna guma otporna na ulje | 1414-0003 | 230 |  |  | 8 | - | 31,75 | 12 | 6 | 1 |
| 16.194.06 | 16.185.06 | New GT: brtva + čepak | 127610-42200 120650-42310 | 106 |  |  | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.26 | 16.185.26 | New T: čepak | 127610-42200 | 114 |  |  | 14,29/16 | - | 65 | 50,1 | 10 | 20 |




Unutarnje pumpe ANCOR

| Kat.broj | | Oprema | Ref. original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/vanjski) mm | Ø A mm | Ø B mm | C mm | Lis-tovi | Profil br. |
|-------------|----------------------|---|---------------|----------|------|--------|-----------------------------|----------|--------|-------|----------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.00 | 16.185.00 New | - | 2745 | 110 | | | 7,31/8 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.16 | 16.185.16 New | - | 50013 | 113 | | | 8 | - | 31,3 | 11,9 | 6 | 1 |
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | 50010 | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.02 | 16.185.02 New | GX: Brtva + zrno | 50021 | 121 | | | 12 | 12 | 39,6 | 19,2 | 6 | 4 |
| 16.194.31 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | 50010 | 200 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 50007 | 107 | | | 14,29/16 | 14,29/16 | 57 | 31,6 | 12 | 26 |
| 16.194.25 | - | T: čepak | 5022 | 104 | | | 14,29/16 | - | 57 | 50,2 | 12 | 26 |
| 16.194.34 | - | GT: brtva + čep; N: nitrilna guma otporna na ulje | 50005; 50405 | 205 | | | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.35 | - | GT: brtva + čep; N: nitrilna guma otporna na ulje | 50407 | 207 | | | 14,29/16 | - | 57 | 31,6 | 12 | 26 |
| 16.194.36 | - | T: čepak; N: uljeotporna nitrilna guma | 50009 | 214 | | | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.40 | - | T: čepak | 50015 | 115T | | | 22,5/25,4 | - | 95 | 88,5 | 9 | 13 |
| 16.194.13 | 16.185.13 New | - | 50016 | 129 | | | 12,75 | 12,75 | 50,8 | 22,1 | 6 | 7 |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | 50020 | 120 | | | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.17 | - | GT: brtva + čepak | 50003 | 103 | | | 15,9 | 15,9 | 62 | 31,7 | 12 | 22 |
| 16.194.24 | 16.185.24 New | T: čepak | 50035 | 135T | | | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.26 | 16.185.26 New | T: čepak | 50009 | 114 | | | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.07 | - | GT: brtva + čepak | 50005 | 105 | | | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | 50045 | 145 | | | 22,5/25,4 | - | 95 | 88,5 | 12 | 15 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + zrno; X: zrno; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.

OBERDORFER unutarnje pumpe



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Lis- tovi | Profil br. |
|-------------|----------------------|--|---------------|----------|------|--------|------------------------------------|--------|-----------|---------|--------------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.10 | - | T: čepak | 6603 | 102 | | | 15,9/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | 8922 | 120 | | | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.16 | 16.185.16 New | - | 24880178 | 113 | | | 8 | - | 31,3 | 11,9 | 6 | 1 |
| 16.194.38 | 16.185.38 New | - | 6617 | 138 | | | 7,31/8 | - | 51,3 | 22 | 6 | 8 |
| 16.194.36 | - | T: čepak; N: uljeotporna nitrilna guma | 7441 | 214 | | | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.00 | 16.185.00 New | - | 6617 | 110 | | | 7,31/8 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.09 | 16.185.09 New | CGT: ključ + brtva + čep | B6620 | 108 | | | 15,93/16 | - | 57 | 31,6 | 12 | 26 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 7441 | 106 | | | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.24 | 16.185.24 New | T: čepak | 7054; J050035 | 135T | | | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.26 | 16.185.26 New | T: čepak | 7441 | 114 | | | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.37 | 16.185.37 New | GT: brtva + čepak | C7441 | 206 | | | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.07 | - | GT: brtva + čepak | C7054 | 105 | | | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |


Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.

Generatori Kohler

| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|----------|------------------|----------|------|--------|------------------------------------|--------|--------|---------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.48 | 16.185.48 New | G: brtva | 229826 | 165 | | | 15,95 | 15,95 | 62,2 | 22,4 | 12 | 22 |
| 16.194.13 | 16.185.13 New | - | 250872 229955 | 129 | | | 12,75 | 12,75 | 50,8 | 22,1 | 6 | 7 |
| 16.194.55 | 16.185.55 New | - | 359978 | 190 | | | 12,2 | 12,2 | 19 | 40 | 6 | 4 |
| 16.194.06 | - | - | - | 106 | | | 14,29/16 | - | 65 | 50,2 | 8 | 11 |

Dodaci: G: brtva. Dodaci: G: brtva; GT: brtva + čep; GX: brtva + zrno; X: zrno; CGT: klin + brtva + čep; N: uljeotporna nitrilna guma; T: čep.


Generatori ONAN



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|--|--|----------|------|--------|---------------------------------------|----------|--------|-------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | 132-0859 | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.02 | 16.185.02 New | GX: Brtva + zrno | 132-0310; OE132-0311 | 121 | | | 12 | 12 | 39,6 | 19,2 | 6 | 4 |
| 16.194.31 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | 132-0859 | 200 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 132-0162; 08-21-1201 | 107 | | | 14,29/16 | 14,29/16 | 57 | 31,6 | 12 | 26 |
| 16.194.17 | - | GT: brtva + čepak | 132-0117/ 132-0317 | 103 | | | 15,9 | 15,9 | 62 | 31,7 | 12 | 22 |
| 16.194.55 | 16.185.55 New | - | OE132-0395; OE132-0407; OE132-0415; OE132-0430; OE132-0493 | 190 | | | 12,2 | 12,2 | 19 | 40 | 6 | 4 |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | 132-0349 | 120 | | | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.66 | - | G: brtva | 132-0358 | 166 | | | 12,8 | 12,8 | 56,6 | 19,8 | 12 | - |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 132-0436 | 106 | | | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.24 | 16.185.24 New | T: čepak | 500135 | 135T | | | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.


DETROIT Motori



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|----------------------|--------------|----------|------|--------|---------------------------------------|--------|------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 5193602 | 106 | | | 14,29/16 | 65 | 50,2 | 8 | 11 |
| 16.194.24 | 16.185.24 New | T: čepak | 8924838 | 135T | | | 22,5/25,4 | 95 | 63,1 | 12 | 15 |
| 16.194.07 | - | GT: brtva + čepak | 5193553 | 105 | | | 22,5/25,4 | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | 5196168 | 145 | | | 22,5/25,4 | 95 | 88,5 | 12 | 15 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.


CATERPILLAR brodskih motora



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|---|--------------------------|----------|------|--------|------------------------------------|----------|--------|-------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.05 | 16.185.05 New | - | - | 107 | | | 14,29/16 | 14,29/16 | 57 | 31,6 | 12 | 26 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 263-7536 | 106 | | | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.24 | 16.185.24 New | T: čepak | 5N9360;5L6042; 1W9046 | 135T | | | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.26 | 16.185.26 New | T: čepak | 7C-3286 | 114 | | | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.37 | 16.185.37 New | GT: brtva + čep; N: nitrilna guma otporna na ulje | 3N1906 | 206 | | | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.07 | - | GT: brtva + čepak | 1L4774 | 105 | | | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | 4L8470 | 145 | | | 22,5/25,4 | - | 95 | 88,5 | 12 | 15 |
| 16.194.52 | - | - | 3N4859 | 152 | | | 20,2 | - | 95 | 88,5 | 12 | 15 |
| 16.194.57 | - | - | 3N5895 | 177.GT | | | 14,29/16 | - | 65,2 | 75,65 | 8 | 11 |
| 16.194.15 | - | - | 1W5664; OE7E0321 | 164 | | | 20,1 | - | 84 | 73,5 | 12 | 24 |
| 16.194.61 | - | GX: Brtva + zрно | 1539123 | 179 | | | 20,7 | - | 114,3 | 109,5 | 10 | 18 |


Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.

Unutarnje pumpe JOHNSON PUMP



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listo- vi | Profil br. |
|-------------|----------------------|----------------------|--------------|----------|------|--------|------------------------------------|--------|--------|-------|--------------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | 09-702B | 120 | | | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.64 | - | GX: Brtva + zрно | 09-705BT-1 | 182 | | | 20,7 | - | 94,5 | 101,5 | 12 | 15 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.




Generatori WESTERBEKE

| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|-------------------|------------------------|----------|------|--------|---------------------------------|----------|--------|------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.66 | - | G: brtva | 33100; 11764; 33112 | 166 | | | 12,8 | 12,8 | 56,6 | 19,8 | 12 | - |
| 16.194.02 | 16.185.02 New | GX: Brtva + zrno | 46622; 32620 | 121 | | | 12 | 12 | 39,6 | 19,2 | 6 | 4 |
| 16.194.48 | 16.185.48 New | G: brtva | 302875 | 165 | | | 15,95 | 15,95 | 62,2 | 22,4 | 12 | 22 |
| 16.194.17 | - | GT: brtva + čepak | 33104; 11907; 11418 | 103 | | | 15,9 | 15,9 | 62 | 31,7 | 12 | 22 |
| 16.194.03 | 16.185.03 New | GX: Brtva + zrno | 34440 | 101 | | | 12,17 | 12,17 | 50,8 | 22,1 | 6 | 7 |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 302571 | 107 | | | 14,29/16 | 14,29/16 | 57 | 31,6 | 12 | 26 |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | 33779 | 120 | | | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.


YAMAHA / SOLE brodskih motora



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|---|--------------------------------------|----------|------|--------|---------------------------------|----------|--------|------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 351.11.008 | 107 | | | 14,29/16 | 14,29/16 | 57 | 31,6 | 12 | 26 |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | 6TA-12457-00 | 120 | | | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.17 | - | GT: brtva + čepak | YSC-101-03-01- OC | 103 | | | 15,9 | 15,9 | 62 | 31,7 | 12 | 22 |
| 16.194.20 | 16.185.20 New | X: Zrno | Mini 11-17-23-26- 34-48; 31211008 | 123 | | | 12 | - | 52 | 25 | 6 | 7 |
| 16.194.21 | - | X: Zrno | 11-16-25-31-45 KS; 32111008 | 131 | | | 10 | - | 39,6 | 19,2 | 6 | 4 |
| 16.194.23 | - | - | - | 124 | | | 14,29/16 | - | 57 | 48,2 | 12 | 26 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 347.11.008 | 106 | | | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.37 | 16.185.37 New | GT: brtva + čep; N: nitrilna guma otporna na ulje | 347.11.008 | 206 | | | 14,29/16 | - | 65 | 50,2 | 8 | 11 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.


PERKINS brodskih motora



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Lis- tovi | Profil br. |
|-------------|----------------------|---|------------------------------------|----------|------|--------|------------------------------------|---------------|-----------|---------|--------------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | 24880272 | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.04 | 16.185.04 New | GX: Brtva + zrno | 24880194 | 116 | | | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.31 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | 24990272 | 200 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.33 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | 24880194 | 216 | | | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 0460038 / 24880190 | 107 | | | 14,29 / 16 | 14,29 / 16 | 57 | 31,6 | 12 | 26 |
| 16.194.62 | - | G: brtva | 119574-42550 | 162 | | | 22,5/25,4 | - | 65.8 | 80 | 12 | 21 |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | NA900012 | 120 | | | 15.9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.17 | - | GT: brtva + čepak | NA9000107 / 24880178 | 103 | | | 15,9 | 15,9 | 62 | 31,7 | 12 | 22 |
| 16.194.44 | - | GX: Brtva + zrno | 24880194 | 156 | | | 12,7 | - | 51,8 | 22 | 10 | 9 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 24880031 | 106 | | | 14,29 / 16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.24 | 16.185.24 New | T: čepak | 7054 | 135T | | | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.26 | 16.185.26 New | T: čepak | 04600247 / 24880031 / 460024 | 114 | | | 14,29 / 16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.37 | 16.185.37 New | GT: brtva + čep; N: nitrilna guma otporna na ulje | 24880031 | 206 | | | 14,29 / 16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.07 | - | GT: brtva + čepak | 460027 | 105 | | | 22,5 / 25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | 460027 | 145 | | | 22,5 / 25,4 | - | 95 | 88,5 | 12 | 15 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.


RENAULT brodskih motora



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/vanjski) mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|---|--|----------|------|--------|-----------------------------|--------|-------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | |
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | RC16D | 100 | | | 9,5 | 39,6 | 18,94 | 6 | 4 |
| 16.194.10 | - | T: čepak | 48300008 | 102 | | | 15,9/16 | 65 | 50,2 | 8 | 11 |
| 16.194.11 | - | - | Svi i Renault 20/80HP 48300037; 48300055 | 127 | | | 10 | 50,8 | 22,1 | 6 | 7 |
| 16.194.12 | - | - | 4830006/07 | 128 | | | 17 | 66 | 32 | 8 | 11 |
| 16.194.31 | - | GX: brtva + zrno; N: uljeotporna nitrilna guma | RC16D | 200 | | | 9,5 | 39,6 | 18,94 | 6 | 4 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | RC320D | 106 | | | 14,29/16 | 65 | 50,2 | 8 | 11 |
| 16.194.37 | 16.185.37 New | GT: brtva + čep; N: nitrilna guma otporna na ulje | RC320D | 206 | | | 14,29/16 | 65 | 50,2 | 8 | 11 |
| 16.194.07 | - | GT: brtva + čepak | RC210D | 105 | | | 22,5/25,4 | 96 | 63,1 | 9 | 13 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.


LOMBARDINI Motori



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|-------------------|--------------|----------|------|--------|-----------------------------|--------|--------|-------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | 875807 | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.02 | 16.185.02 New | GX: Brtva + zrno | 42001940 | 121 | | | 12 | 12 | 39,6 | 19,2 | 6 | 4 |
| 16.194.03 | 16.185.03 New | GX: Brtva + zrno | 42001960 | 101 | | | 12,17 | 12,17 | 50,8 | 22,1 | 6 | 7 |
| 16.194.04 | 16.185.04 New | GX: Brtva + zrno | 42001930 | 116 | | | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.43 | 16.185.43 New | X: Zrno | 42002040 | 146 | | | 12,17 | - | 51,8 | 22 | 10 | 9 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 42002060 | 106 | | | 14,29/16 | - | 65 | 50,2 | 8 | 11 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.


VETUS brodskih motora



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|---|--------------|----------|------|--------|------------------------------------|----------|--------|-------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.01 | 16.185.01 New | GX: Brtva + zрно | 501 | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.02 | 16.185.02 New | GX: Brtva + zрно | 601 | 121 | | | 12 | 12 | 39,6 | 19,2 | 6 | 4 |
| 16.194.03 | 16.185.03 New | GX: Brtva + zрно | 801 | 101 | | | 12,17 | 12,17 | 50,8 | 22,1 | 6 | 7 |
| 16.194.04 | 16.185.04 New | GX: Brtva + zрно | 101 | 116 | | | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.31 | - | GX: brtva + zрно; N: uljeotporna nitrilna guma | 501 | 200 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.43 | 16.185.43 New | X: Zрно | 701 | 146 | | | 12,17 | - | 51,8 | 22 | 10 | 9 |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 201 | 107 | | | 14,29/16 | 14,29/16 | 57 | 31,6 | 12 | 26 |
| 16.194.34 | - | GT: brtva + čep; N: nitrilna guma otporna na ulje | 901 | 205 | | | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.36 | - | T: čepak; N: uljeotporna nitrilna guma | 301 | 214 | | | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.13 | 16.185.13 New | - | 101 | 129 | | | 12,75 | 12,75 | 50,8 | 22,1 | 6 | 7 |
| 16.193.73 | 16.186.73 New | N: nitrilna guma otporna na ulje | 50011 | 238 | | | 7,31/8,07 | - | 51,3 | 22 | 6 | 8 |
| 16.194.41 | - | - | 401 | 232 | | | 8 | - | 44,6 | 13 | 6 | 5 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 301 | 106 | | | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.26 | 16.185.26 New | T: čepak | 301 | 114 | | | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.07 | - | GT: brtva + čepak | 901 | 105 | | | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | 801 | 145 | | | 22,5/25,4 | - | 95 | 88,5 | 12 | 15 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.


Motori diesel NANNI



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listo- vi | Profil br. |
|----------------|----------------------|-------------------|--|----------|------|--------|------------------------------------|--------------|-----------|-------|--------------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | 908200300 | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.02 | 16.185.02 New | GX: Brtva + zrno | FK2,40E/ HE,2,60H, KLA,L30,3.90; OE970434013 | 121 | | | 12 | 12 | 39,6 | 19,2 | 6 | 4 |
| 16.194.43 | 16.185.43 New | X: Zrno | FK3, 2345H2, 2.50HE, 2.60HE, 3.75HE, 3.90H/HE, 4.110.H, 4.410.M | 146 | | | 12,17 | - | 51,8 | 22 | 10 | 9 |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 3.100HE, 3.110HE, 4.110HE, 4.150HE, 4.180, 4.190HE, 4.200HE, MB180,220,330; 970604530 | 107 | | | 14,29/16 | 14,29/ 16 | 57 | 31,6 | 12 | 26 |
| 16.194.11 | - | - | 48300250 | 127 | | | 10 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.12 | - | - | 48300251 | 128 | | | 17 | - | 66 | 32 | 8 | 11 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 4.230, 4.240, 4.380, 5.300, 970312423 | 106 | | | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.24 | 16.185.24 New | T: čepak | 1300, 1600 | 135T | | | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.26 | 16.185.26 New | T: čepak | 4.220HE, 4330TDi, 4.440E, 5.280HE, 5.250TDi, 5.300/T, 6.280HE, 6.570T, 6.660E/LE, 970544310 | 114 | | | 14,29/16 | - | 65 | 50,1 | 10 | 20 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.


SOLE' / DIESEL motori



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|----------|--------------|----------|------|--------|------------------------------------|--------|------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | |
| 16.194.45 | - | - | 39411008 | 161 | | | 22,5/25,4 | 95 | 63,1 | 12 | 15 |
| 16.194.26 | 16.185.26 New | T: čepak | 34711008 | 114 | | | 14,29/16 | 65 | 50,1 | 10 | 20 |












Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.

DJ PUMP unutarnje pumpe




| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-------------|----------------------|-----------------------------|--------------|----------|------|--------|------------------------------------|--------------|--------|-------|---------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | 08-41-0601 | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.02 | 16.185.02 New | GX: Brtva + zrno | 08-31-0601 | 121 | | | 12 | 12 | 39,6 | 19,2 | 6 | 4 |
| 16.194.03 | 16.185.03 New | GX: Brtva + zrno | 08-39-0601 | 101 | | | 12,17 | 12,17 | 50,8 | 22,1 | 6 | 7 |
| 16.194.04 | 16.185.04 New | GX: Brtva + zrno | 09-108-0601 | 116 | | | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 08-21-1201 | 107 | | | 14,29/16 | 14,29/ 16 | 57 | 31,6 | 12 | 26 |
| 16.194.09 | 16.185.09 New | CGT: ključ + brtva + čep | 08-22-1201 | 108 | | | 15,93/16 | - | 57 | 31,6 | 12 | 26 |
| 16.194.10 | - | T: čepak | 08-46-0801 | 102 | | | 15,9/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.13 | 16.185.13 New | - | 08-37-0601 | 129 | | | 12,75 | 12,75 | 50,8 | 22,1 | 6 | 7 |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | 08-20-1201 | 120 | | | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.17 | - | GT: brtva + čepak | 08-38-1201 | 103 | | | 15,9 | 15,9 | 62 | 31,7 | 12 | 22 |
| 16.194.23 | 16.185.23 New | - | 09-105-1201 | 124 | | | 14,29/16 | - | 57 | 48,2 | 12 | 26 |
| 16.194.29 | - | T: čepak | 09-201-1003 | 109 | | | 16,85/19 | - | 66,5 | 50,6 | 8 | 20 |
| 16.194.40 | - | T: čepak | 086-0901 | 115T | | | 22,5/25,4 | - | 95 | 88,5 | 9 | 13 |
| 16.194.45 | - | - | 09-42-1001 | 161 | | | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.48 | 16.185.48 New | G: brtva | 09-106-1201 | 165 | | | 15,95 | - | 62,2 | 22,4 | 12 | 22 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.

| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|----------------|----------------------|----------------------|--------------|----------|---|---|---------------------------------|--------|--------|-------|---------|---------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.55 | 16.185.55 New | G: brtva | 09-107-0601 | 190 |  |  | 12.2 | 12,2 | 19 | 40 | 6 | 4 |
| 16.194.60 | - | T: čepak | 08-30-1201 | 186 |  |  | 22,5/25,4 | - | 96.5 | 130 | 12 | 15 |
| 16.194.62 | - | G: brtva | 09-44-1201 | 162 |  |  | 22,5/25,4 | - | 65.8 | 80 | 12 | 21 |
| 16.194.64 | - | GX: Brtva + zrno | 08-33-1201 | 182 |  |  | 20.7 | - | 94.5 | 101.5 | 12 | 15 |
| 16.194.66 | - | G: brtva | 08-32-1201 | 166 |  |  | 12.8 | 12,8 | 56.6 | 19.8 | 12 | - |
| 16.194.77 | - | - | 08-14-1001 | 144 |  |  | 22,5/25,4 | - | 117,6 | 88,5 | 9 | 28 |
| 16.194.78 | - | G: brtva | 08-15-1001 | 153 |  | - | 20,2 | - | 117,6 | 88,5 | 9 | 28 |
| 16.194.80 | - | G: brtva | 09-45-1201 | 163 |  |  | 22,5/25,4 | - | 95 | 95 | 12 | 15 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 001-0801 | 106 |  |  | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.24 | 16.185.24 New | T: čepak | 003-1201 | 135T |  |  | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.37 | 16.185.37 New | GT: brtva + čepak | 001-0801N | 206 |  |  | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.07 | - | GT: brtva + čepak | 003-0901 | 105 |  |  | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | 086-1201 | 145 |  |  | 22,5/25,4 | - | 95 | 88,5 | 12 | 15 |
| 16.194.52 | - | - | 088-1201 | 152 |  |  | 20,2 | - | 95 | 88,5 | 12 | 15 |
| 16.194.61 | - | GX: Brtva + zrno | 09-49-1001T | 179 |  |  | 20.7 | - | 114.3 | 109.5 | 10 | 18 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.

CUMMINS Motori









































| Kat.broj Impeler CEF | Impeler OSCULATI | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|----------------------------|----------------------|----------------------|--------------|----------|------|--------|------------------------------------|--------|--------|-------|---------|------------|
| 16.194.55 | 16.185.55 New | G: brtva | 132-0415 | 190 | | | 12,2 | 12,2 | 19 | 40 | 6 | 4 |
| 16.194.63 | - | G: brtva | 3974456 | 181 | | | 16,1 | - | 84 | 73 | 12 | 24 |
| 16.194.64 | - | GX: Brtva + zrno | 4933743 | 182 | | | 20,7 | - | 94,5 | 101,5 | 12 | 15 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 650607 | 106 | | | 14,29 / 16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.26 | 16.185.26 New | T: čepak | 879194186 | 114 | | | 14,29 / 16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.07 | - | GT: brtva + čepak | 10556540 | 105 | | | 22,5 / 25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | 8503 | 145 | | | 22,5 / 25,4 | - | 95 | 88,5 | 12 | 15 |
| 16.194.52 | - | - | 217308 | 152 | | | 20,2 | - | 95 | 88,5 | 12 | 15 |


Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.

JMP unutarnje pumpe

| Kat.broj Impeler CEF | Impeler OSCULATI | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|----------------------------|----------------------|----------------------|--------------|----------|------|--------|------------------------------------|------------|--------|-------|---------|------------|
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | 7001-01 | 100 | | | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.02 | 16.185.02 New | GX: Brtva + zrno | 7000-01 | 121 | | | 12 | 12 | 39,6 | 19,2 | 6 | 4 |
| 16.194.03 | 16.185.03 New | GX: Brtva + zrno | 7050-01 | 101 | | | 12,17 | 12,17 | 50,8 | 22,1 | 6 | 7 |
| 16.194.04 | 16.185.04 New | GX: Brtva + zrno | 7051-01 | 116 | | | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | 7100-01 | 107 | | | 14,29 / 16 | 14,29 / 16 | 57 | 31,6 | 12 | 26 |
| 16.194.10 | - | T: čepak | 7410-01 | 102 | | | 15,9 / 16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.13 | 16.185.13 New | - | 7052-01 | 129 | | | 12,75 | 12,75 | 50,8 | 22,1 | 6 | 7 |

| Kat.broj | | Oprema | Ref.original | Ref.CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|-----------|----------------------|----------------------|--------------|---------|---|---|---------------------------------|--------|--------|-------|---------|------------|
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | 7300-01 | 120 |  |  | 15.9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.22 | - | - | 6000-01 | 130 |  |  | 8 | - | 31,75 | 12 | 6 | 3 |
| 16.194.38 | 16.185.38 New | - | 7053-01 | 138 |  |  | 7,31/8 | - | 51,3 | 22 | 6 | 8 |
| 16.194.40 | - | T: čepak | 8200-01 | 115T |  |  | 22,5/25,4 | - | 95 | 88,5 | 9 | 13 |
| 16.194.43 | 16.185.43 New | X: Zrno | 7070-01 | 146 |  |  | 12,17 | - | 51,8 | 22 | 10 | 9 |
| 16.194.44 | - | GX: Brtva + zrno | 7071-01 | 156 |  |  | 12,7 | - | 51,8 | 22 | 10 | 9 |
| 16.194.45 | - | - | 7420-01 | 161 |  |  | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.48 | 16.185.48 New | G: brtva | 7172-01 | 165 |  |  | 15,95 | - | 62,2 | 22,4 | 12 | 22 |
| 16.194.55 | 16.185.55 New | G: brtva | 7013-01 | 190 |  |  | 12,2 | 12,2 | 19 | 40 | 6 | 4 |
| 16.194.66 | - | G: brtva | 7110-01 | 166 |  |  | 12,8 | 12,8 | 56,6 | 19,8 | 12 | - |
| 16.194.77 | - | - | 9001-01 | 144 |  |  | 22,5/25,4 | - | 117,6 | 88,5 | 9 | 28 |
| 16.194.80 | - | G: brtva | 8326-01 | 163 |  |  | 22,5/25,4 | - | 95 | 95 | 12 | 15 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | 7400-01 | 106 |  |  | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.24 | 16.185.24 New | T: čepak | 8100-01 | 135T |  |  | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.26 | 16.185.26 New | T: čepak | 7400-01 | 114 |  |  | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.07 | - | GT: brtva + čepak | 8000-01 | 105 |  |  | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | 8301-01 | 145 |  |  | 22,5/25,4 | - | 95 | 88,5 | 12 | 15 |
| 16.194.52 | - | - | 8300-01 | 152 |  |  | 20,2 | - | 95 | 88,5 | 12 | 15 |
| 16.194.57 | - | GT: brtva + čepak | 7446-01 | 177.GT |  |  | 14,29/16 | - | 65,2 | 75,65 | 8 | 11 |


KAISHYAMA Motori



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listovi | Profil br. |
|----------------|----------------------|------------------------|--------------|----------|---|---|---------------------------------|----------|--------|-------|---------|---------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | SP-30 | 107 |  |  | 14,29/16 | 14,29/16 | 57 | 31,6 | 12 | 26 |
| 16.194.04 | 16.185.04 New | GX: Brtva + zrno | 3KL | 116 |  |  | 12,66 | - | 50,8 | 22,1 | 6 | 7 |
| 16.194.13 | 16.185.13 New | - | 2QM | 129 |  |  | 12,75 | 12,75 | 50,8 | 22,1 | 6 | 7 |
| 16.194.29 | - | T: čepak | AH-70 | 109 |  |  | 16,85/19 | - | 66,5 | 50,6 | 8 | 20 |
| 16.194.80 | - | G: brtva | SP-300 | 163 |  |  | 22,5/25,4 | - | 95 | 95 | 12 | 15 |
| 16.194.84 | - | CG: klinčić + brtva | SP-30K | 170 |  |  | 16 | - | 57 | 31,6 | 12 | 26 |
| 16.194.01 | 16.185.01 New | GX: Brtva + zrno | YS12 | 100 |  |  | 9,5 | - | 39,6 | 18,94 | 6 | 4 |
| 16.194.14 | 16.185.14 New | GT: brtva + čepak | SP-60 | 120 |  |  | 15,9 | 15,9 | 65,2 | 41,3 | 12 | 21 |
| 16.194.40 | - | T: čepak | SP-280 | 115T |  |  | 22,5/25,4 | - | 95 | 88,5 | 9 | 13 |
| 16.194.45 | - | - | SP-130 | 161 |  |  | 22,5/25,4 | - | 95 | 63,1 | 12 | 15 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | SP-70 | 106 |  |  | 14,29/16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.26 | 16.185.26 New | T: čepak | SP-70 | 114 |  |  | 14,29/16 | - | 65 | 50,1 | 10 | 20 |
| 16.194.07 | - | GT: brtva + čepak | SP-200/220 | 105 |  |  | 22,5/25,4 | - | 96 | 63,1 | 9 | 13 |
| 16.194.08 | - | GT: brtva + čepak | SP-280 | 145 |  |  | 22,5/25,4 | - | 95 | 88,5 | 12 | 15 |
| 16.194.52 | - | - | FT-A6 | 152 |  |  | 20,2 | - | 95 | 88,5 | 12 | 15 |


Dodaci: G: brtva; GT: brtva + čep; GX: brtva + zrno; X: zrno; CGT: ključ + brtva + čep; CG: ključ + brtva; N: uljeotporna nitrilna guma; T: čep.

NIKKISO motori



| Kat.broj | | Oprema | Ref.original | Ref. CEF | Foto | Umetak | Ø A (unutrašnji/ vanjski) mm | Ø A mm | Ø B mm | C mm | Listo- vi | Profil br. |
|----------------|----------------------|-------------------|--------------|----------|------|--------|---------------------------------|------------|--------|------|--------------|------------|
| Impeler CEF | Impeler OSCULATI | | | | | | | | | | | |
| 16.194.05 | 16.185.05 New | GT: brtva + čepak | F15CBC | 107 | | | 14,29 / 16 | 14,29 / 16 | 57 | 31,6 | 12 | 26 |
| 16.194.06 | 16.185.06 New | GT: brtva + čepak | F20CBC | 106 | | | 14,29 / 16 | - | 65 | 50,2 | 8 | 11 |
| 16.194.07 | - | GT: brtva + čepak | F40CBC | 105 | | | 22,5 / 25,4 | - | 96 | 63,1 | 9 | 13 |

Oprema: G: brtva; GT: brtva + čep; GX: brtva + grano; X: grano; CGT: osigurač + brtva + čep; N: nitrilna guma otporna na ulje; T: čep.



Ekstraktor za impelere od nerđajućeg čelika

Omogućavaju vađenje impelera od neoprena bez oštećivanja ležišta pumpe.

| Kat.broj | Za pumpe |
|-----------|-------------------------|
| 16.191.01 | sa priključkom do 1" |
| 16.191.02 | sa priključkom preko 1" |



